



VSE Project Number: U4584.0009.251

March 24, 2025

E&M Solar, LLC  
ATTENTION: Michael Younghans  
2236 Spiritwood Lane  
Bellvue, CO 80512

**REFERENCE: Robert Pratt Residence: 26730 County Road 14, Steamboat Springs, CO 80487**  
**E&M Solar, LLC Project: Pratt01**  
**Solar Array Installation**

To Whom It May Concern:

We have reviewed the existing structure at the above referenced site. The purpose of our review was to determine the adequacy of the existing structure to support the proposed installation of solar panels on the roof as shown on the panel layout plan.

Based upon our review and the as-built plans from Robb Studio Inc., dated 03/02/2023, we conclude the existing structure is adequate to support the proposed solar panel installation.

#### **Design Parameters**

Code: International Residential Code, 2021 Edition  
Risk Category: II  
Design wind speed, Vult: 106 mph (3-sec gust)  
Wind exposure category: C  
Ground snow load, Pg: 111 psf  
Seismic design category: D

#### **Existing Roof Structure**

Roof structure: 2x10 rafters @ 24" o.c.  
Roofing material: metal seam  
Roof slope: 44°

#### **Connection to Roof**

Mounting connection: (1) S-5! U Clamp to min. 26 ga steel roofing at max. 16" o.c. along rails

- Install (2) rails per row of panels, evenly spaced from panel center
- Panel length perpendicular to the rails shall not exceed 57 in
- Rail cantilever shall not exceed the lesser of 50% of the connection spacing or max cantilever allowed by manufacturer
- Connections shall be staggered so as not to overload any existing structural member

**Note: Contractor shall verify min. metal gauge prior to installation of the solar panels.**

#### **Conclusions**

Based upon our review, we conclude the existing structure is adequate to support the proposed solar panel installation. See attached calculations.



The solar array will be flush-mounted (no more than 10" above the roof surface) and parallel to the roof surface. Thus, we conclude that any additional wind loading on the structure related to the addition of the proposed solar array is negligible. The attached calculations verify the capacity of the connections of the solar array to the existing roof against wind (uplift), the governing load case. Regarding seismic loads, we conclude that any additional forces will be small. The installation of the solar panels represents an increase in the total weight (and resulting seismic load) of 8.8%. Increases in lateral forces less than 10% are considered acceptable. Thus the existing lateral force resisting system is permitted to remain unaltered.

### **Limitations**

Installation of the solar panels must be performed in accordance with manufacturer recommendations. All work performed must be in accordance with accepted industry-wide methods and applicable safety standards. The contractor must notify Vector Structural Engineering, LLC should any damage, deterioration or discrepancies between the as-built condition of the structure and the condition described in this letter be found. The use of solar panel support span tables provided by others is allowed only where the building type, site conditions, site-specific design parameters, and solar panel configuration match the description of the span tables. The design of the solar panels, solar racking (mounts, rails, etc.) and electrical engineering is the responsibility of others. Waterproofing around the roof penetrations is the responsibility of others. Vector Structural Engineering assumes no responsibility for improper installation of the solar array. Vector Structural Engineering shall be notified of any changes from the approved layout prior to installation.

VECTOR STRUCTURAL ENGINEERING, LLC

CO Firm License: 20181009799



---

Eric S. Sumsion, P.E.

CO License: 56167 - Expires: 10/31/2025

Project Engineer

Enclosures

ESS/crs



Copyright © 2025 Vector Structural Engineering, LLC  
This workbook and files generated from this workbook contain  
proprietary information belonging to Vector Structural Engineering,  
LLC, and may be neither wholly nor partially copied or reproduced  
without the prior written permission of Vector Structural  
Engineering, LLC.

**PROJECT:** Robert Pratt Residence

**JOB NO.:** U4584.0009.251

**SUBJECT:** SEISMIC LOADS

**CHECK INCREASE IN OVERALL SEISMIC LOADS**

Estimated Roof Dead Load	13.9	psf
Roof Area	1500	ft <sup>2</sup>
Wall Dead Load	10	psf
Wall Height	8	ft
Roof Perimeter	160	ft
Existing Seismic Weight	27.2	k
Solar Dead Load	3.0	psf
Solar Area	798.4824	ft <sup>2</sup>
% Roof Covered	53%	
Proposed Seismic Weight	29.6	k
Add'l Seismic Weight	8.8%	

The installation of the solar panels represents an increase in the total weight (and resulting seismic load) of 8.8%.  
Increases in lateral forces less than 10% are considered acceptable.



Copyright © 2025 Vector Structural Engineering, LLC  
 This workbook and files generated from this workbook contain  
 proprietary information belonging to Vector Structural Engineering, LLC,  
 and may be neither wholly nor partially copied or reproduced without the  
 prior written permission of Vector Structural Engineering, LLC.

**PROJECT:** Robert Pratt Residence  
**JOB NO.:** U4584.0009.251

**SUBJECT:** WIND PRESSURE

Calculations per ASCE 7-16

**Calculate Velocity Pressures** (Chapter 26)

$$q_h = 0.00256 K_h K_{zt} K_e K_d V^2 \quad (\text{Eq. 26.10-1})$$

Roof Plane	Risk Cat.	Wind Speed, $V_{ult}$ [mph]	Wind Exp. Cat.	Roof Height, $h$ [ft]	$z_g$ [ft]	$\alpha$	$K_h$	$K_{zt}$	$K_e$	$K_d$	$q_h$ [psf]	Racking Type
Typical	II	106	C	25	900	9.5	0.95	1.00	0.77	0.85	17.8	Railed

**Calculate Component and Cladding Pressures** (Chapters 29 and 30)

'-' pressure descriptions act away from panels (uplift), '+' pressure descriptions act towards panel (downward)

Pressure Description	$q_h$ [psf]	C&C Category	$GC_p$	$Y_E$	$Y_a$	$Y_c$	$Y_p$	Pressure, $P$ (1.0 W) [psf]
Typical: - Zone 1 (Exposed, Landscape)	17.8	Gable Roofs $27^\circ < \theta \leq 45^\circ$	1.8	1.5	0.8	1.0	1.0	38.4
Typical: - Zone 2e (Exposed, Landscape)	17.8	Gable Roofs $27^\circ < \theta \leq 45^\circ$	1.8	1.5	0.8	1.0	1.0	38.4
Typical: - Zone 2n (Exposed, Landscape)	17.8	Gable Roofs $27^\circ < \theta \leq 45^\circ$	2.0	1.5	0.8	1.0	1.0	42.6
Typical: - Zone 2r (Exposed, Landscape)	17.8	Gable Roofs $27^\circ < \theta \leq 45^\circ$	1.8	1.5	0.8	1.0	1.0	38.4
Typical: - Zone 3e (Exposed, Landscape)	17.8	Gable Roofs $27^\circ < \theta \leq 45^\circ$	3.0	1.5	0.8	1.0	1.0	64.0
Typical: - Zone 3r (Exposed, Landscape)	17.8	Gable Roofs $27^\circ < \theta \leq 45^\circ$	2.0	1.5	0.8	1.0	1.0	42.6



Copyright © 2025 Vector Structural Engineering, LLC  
 This workbook and files generated from this workbook contain  
 proprietary information belonging to Vector Structural  
 Engineering, LLC, and may be neither wholly nor partially copied  
 or reproduced without the prior written permission of Vector  
 Structural Engineering, LLC.

**PROJECT:** Robert Pratt Residence  
**JOB NO.:** U4584.0009.251

**SUBJECT:** CONNECTION

**Calculate Uplift Forces on Connection**

	Pressure (0.6 Dead - 0.6 Wind) (psf)	Max Trib. Width <sup>1</sup> (ft)	Max Trib. Area <sup>2</sup> (ft <sup>2</sup> )	Max Uplift Force (lbs)
- Zone 1 (L)	21.2	1.3	3.1	67
- Zone 2e (L)	21.2	1.3	3.1	67
- Zone 2n (L)	23.8	1.3	3.1	75
- Zone 2r (L)	21.2	1.3	3.1	67
- Zone 3e (L)	36.6	1.3	3.1	115
- Zone 3r (L)	23.8	1.3	3.1	75

(P) = Portrait orientation relative to rails, (L) = Landscape orientation relative to rails

**Calculate Connection Capacity**

Roof Connector:	S-5! U Clamp
Additional Connection Info:	to min. 26 ga steel roofing
Ultimate Capacity <sup>3</sup> [lbs/in]:	429
Factor of Safety:	3
Qty. of Connectors:	1
Prying Coefficient:	1
Total Capacity [lbs]:	143

**Determine Result**

Maximum Demand:	115
Connection Capacity:	143

Result: **Capacity > Demand, Connection is adequate.**

**Notes**

1. 'Max Trib. Width' is the width along the rails tributary to the connection.
2. 'Max Trib Area' is the product of the 'Max. Trib Width' and 1/2 the panel width/height perpendicular to the rails. This installation uses (2) rails per row of panels. Length of the panels perpendicular to the rails shall not exceed 57".

3. Ultimate capacity values are from manufacturer testing. Metal gauge is unknown. A conservative thickness has been used. Metal gauge shall be verified in field prior to installation of solar panels. Roof deck model is unknown or has not been tested for this connector. The capacity used is based on conservative values from testing of the connector on similar roof deck model.
4. Install metal roof connector per manufacturer's written instructions with recommended fasteners when indicated.



Copyright © 2025 Vector Structural Engineering, LLC  
 This workbook and files generated from this workbook contain proprietary information belonging to Vector Structural Engineering, LLC, and may be neither wholly nor partially copied or reproduced without the prior written permission of Vector Structural Engineering, LLC.

**PROJECT:** Robert Pratt Residence  
**JOB NO.:** U4584.0009.251

**SUBJECT:** GRAVITY LOADS

**GRAVITY LOADS**

Roof Pitch: **11.6** :12

<b>ROOF DEAD LOAD (D)</b>	Design material weight [psf]	Increase due to pitch	Material weight [psf]
Metal Seam	3.5	1.39	2.5
1/2" Plywood	1.4	1.39	1.0
Framing	3.0		3.0
Insulation	0.0		0.0
1/2" Gypsum Clg.	0.0	1.39	0.0
M, E & Misc	2.0		2.0
Total Existing Roof DL	9.9		
PV Array DL	4.2	1.39	3

**ROOF LIVE LOAD (Lr)**

Existing Design Roof Live Load [psf]	<b>20</b>	ASCE 7-16 Table 4.3-1
Roof Live Load With PV Array [psf]	<b>0</b>	2021 IRC, Section R324.4.1.1

**SNOW LOAD (S):**

Existing w/ Solar Array

Roof Slope [x:12]:	<b>11.6</b>	<b>11.6</b>	
Roof Slope [°]:	<b>44</b>	<b>44</b>	
Ground Snow Load, $p_g$ [psf]	<b>111</b>	<b>111</b>	ASCE 7-16, Section 7.2
Surface Roughness Category:	<b>C</b>	<b>C</b>	ASCE 7-16, Table 7.3-1
Exposure of Roof:	<b>Fully Exposed</b>	<b>Fully Exposed</b>	ASCE 7-16, Table 7.3-1
Exposure Factor, $C_e$ :	<b>0.9</b>	<b>0.9</b>	ASCE 7-16, Table 7.3-1
Thermal Factor, $C_t$ :	<b>1.1</b>	<b>1.1</b>	ASCE 7-16, Table 7.3-2
Risk Category:	<b>II</b>	<b>II</b>	ASCE 7-16, Table 1.5-1
Importance Factor, $I_s$ :	<b>1.0</b>	<b>1.0</b>	ASCE 7-16, Table 1.5-2
Flat Roof Snow Load, $p_f$ [psf]:	<b>77</b>	<b>77</b>	ASCE 7-16, Equation 7.3-1
Minimum Roof Snow Load, $p_m$ [psf]:	<b>0</b>	<b>0</b>	ASCE 7-16, Section 7.3.4
Unobstructed Slippery Surface?	<b>Yes</b>	<b>Yes</b>	ASCE 7-16, Section 7.4
Slope Factor Figure:	<b>Figure 7-2b</b>	<b>Figure 7-2b</b>	ASCE 7-16, Section 7.4
Roof Slope Factor, $C_s$ :	<b>0.43</b>	<b>0.43</b>	ASCE 7-16, Figure 7.4-1
Sloped Roof Snow Load, $p_s$ [psf]:	<b>33</b>	<b>33</b>	ASCE 7-16, Equation 7.4-1
<b>Design Snow Load, S [psf]:</b>	<b>33</b>	<b>33</b>	



Copyright © 2025 Vector Structural Engineering, LLC  
This workbook and files generated from this workbook contain proprietary  
information belonging to Vector Structural Engineering, LLC, and may be neither  
wholly nor partially copied or reproduced without the prior written permission of  
Vector Structural Engineering, LLC.

PROJECT: Robert Pratt Residence  
JOB NO.: U4584.0009.251

SUBJECT: BEAMS

DESIGN LOADS:	Load Types:	Snow	Live	Dead
	Roof	33	20	10
	Solar			4.2

CRITERIA (L)	D <sub>TL</sub>	D <sub>LL</sub>	D <sub>DL</sub>
A <sub>(BLANK)</sub>	120	180	

Abbrev	GRADES		F <sub>bxx</sub> (psi)	F <sub>vxx</sub> (psi)	E <sub>xx</sub> (psi)	g (lb/ft <sup>3</sup> )
DFL#1	DFL#1		1,000	180	1,700,000	32
DFL#2	DFL#2		900	180	1,600,000	32
DF1 (5X)	DFL#1 5X5 & LARGER		1,350	170	1,600,000	32
SPF#2	SPF#2		875	135	1,400,000	26.2
SP#2	SP#2		1,100	175	1,400,000	34.3
24F-V4	24F-V4		2,400	240	1,800,000	32
24F-V8	24F-V8		2,400	240	1,800,000	40
LVL (1.9)	LVL (1.9X106E)		2,600	285	1,900,000	40
LVL (2.0)	LVL (2.0X106E)		2,200	285	2,000,000	42
LSL	LSL (1.3X106E)		1,700	400	1,300,000	42
STL36	GRADE 36 STEEL		21,600	14,400	29,000,000	490
STL46	GRADE 46 STEEL		27,700	16,500	29,000,000	490
STL50	GRADE 50 STEEL		30,000	20,000	29,000,000	490

Label	Length 'L' (ft)	Roof Trib (ft)	Floor Trib (ft)	Wall Trib (ft)	Add'l Live Load (plf)	Add'l Solar Load (plf)	Point Load From	React (A,B)	Dist 'a' (ft)	Point Live Load 'P <sub>LL</sub> ' (lb)	Point Dead Load 'P <sub>DL</sub> ' (lb)	# PLIES	Grade	Size	"BM/HDR"	D CRITERIA	C <sub>r</sub>	C <sub>D</sub>	C <sub>F,V</sub>	R <sub>a</sub> (lb)	R <sub>b</sub> (lb)	M <sub>max</sub> (ft-lb)	M <sub>allow</sub> (ft-lb)	V <sub>max</sub> (lb)	V <sub>allow</sub> (lb)	D <sub>TL</sub> (in)	D <sub>TLallow</sub> (in)	D <sub>LL</sub> (in)	D <sub>LLallow</sub> (in)	1.5DL GLB Camb	Check
Rafter	13.3	2.00				8.3						(1)	SPF#2	2x10			1.15	1.15	1.10	631	631	2104	2269	558	1436	0.486	1.333	0.342	0.889		0.93 M
GL Beams	13.3	6.55				27.3						(1)	24F-V4	5-1/8X18			1.00	1.15	1.00	2068	2068	6889	63653	1602	16974	0.049	1.333	0.035	0.889	STD	0.11 M





**JOB NO.:** U4584.0009.251  
**SUBJECT:** SOLAR LAYOUT

**PROJECT:** Robert Pratt Residence

---

