

KITCHEN HOOD SYSTEM REPORT

DATE: 05/19/2022

JOB NAME:

Steamboat Lake Outpost 608800 Co Rd 129, Clark, CO 80428

(970)291-1656 (970)819-2212 P.O BOX 881681 Steamboat Spgs., CO 80488 Eco.shinefireprevention@gmail.com

TVDE	OE	INISPECTION	ı

	TE OF INSTECTION							
	Annual X Semi-	-Annual	nnual x Recharge Inst				Renovat	ion
INSPECTION REPORT								
	Amerex Ansul Badger			Badger	Buckeye			
	Kiddle Protex Pyro-Chem			Pyro-Chem	Range Guard			
ОТН	ER:							
	Single	х	Double		Triple	Quad		
Multip	le:							
Model	and Serial No.	Ansul R	-102 6 gallons sys	tem				
Locatio	Location: kitchen wall							
Date o	Date of Last Service: 05/19/2022							
	ITEM						N/A	NO
1	System interlocked with building fire alarm						х	
2	Audible / Visual notifications operated						х	
3	Monitoring agency notified when system activated						х	
4	System discharged					х		
5	All seals intact. No evidence of tempering					х		
6	All appliances properly covered with correct nozzles					х		
7								
8	Checked positioning of all nozzles							

9	Hood / Duct penetrations sealed						х					
	ITEM											
10	Grease Accumulation			EXC	ESSIVE		х	HEA	ιVY		NORN	IAL
	Date of Last Hood Clear	ning:	N/A		НС	OD CL	EANE	ON:	05/14/2022	•		
11	Pressure gauge in propo	er range									Х	
12	Checked Actuation Cartridge Weight Date 01/01/22											
13	Cylinder Hydrostatic Te	st Date: 20)19									
14	Inspect cylinder & mou	nt								х		
15	System cylinder weight or liquid level "OK"							х				
16	Operated System from terminal link						х					
17	Checked travel of cable & link position						х					
18	Fusible Links 360 ⁰ 450 ⁰ 5											
19	Replaced fusible links. Mfg. Date new 2021 fusible link											
20	Checked operation of manual release						х					
21	Checked operation of micro-switch						х					
22	Checked operation of gas valve						х					
23	Gas shut-down upon activation of the system					х						
24	Piping / Conduit securely bracketed						х					
25	Nozzles Cleaned					х						
26	Proper nozzle caps / covers in place					х						
27	Proper clearance flame to filters					х						
28	Exhaust Fan In operating order						х					

29	Electrical under hood shutdown "OK"	х		
30	Manual and Remote set seals in place	Х		
31	System operational and armed	х		
32	Slave system operational and armed		х	
33	System operation "OK"	х		
34	Fan warning sign on hood			х
35	Class K Fire Extinguisher in cooking area	х		
36	2A water type / wet chem. Type for solid fuel		х	
37	Water hose in area of solid fuel		х	
38	Proper ABC Fire Extinguisher for other areas	х		
39	System installed per U.L. 300 Standard	х		
40	System rework required			х
41	System reset and operable	Х		

NOTE:

COMMENTS

Piping system flushed pass Actuation cardtridge replaced Tanks refilled with fresh Ansulex 6 gallons Replaced 1 breaker bar in Ansul pull station

COOKING APPLIANCES LEFT TO RIGHT						
Range,Griddel,Charbroiler,Fryer,Fryer						
*At least semiannually and after any system activation. Maintenance should conduct in accordance with the manufacture's design, installation, and maintenance manual. [see NFPA 17A(17), Sec. 7-3.3]. * the following parts of wet chemical extinguishing systems shall be subject to a hydrostatic pressure test at intervals not exceeding 12 years: 1. Wet chemical containers, 2. Auxiliary pressure containers, 3. Hose assemblies. [see NFPA 17A(17), Sec. 7-5.1]. Wet chemical agent removed from the containers prior to hydrostatic testing shall be discarded[see						
NFPA 17A(17), Sec. 7-5.3].*						
TECHNICIAN SIGNATURE:	DATE: 05/19/2022					