SANDERS GRAVEL PIT

LEVEL 2 TRAFFIC IMPACT STUDY

Project Location:

26650 Wheeler Creek Ln Routt County, CO

Prepared By:

APEX Consulting Engineers, LLC 1000 N 9th Street, Suite 44 Grand Junction, CO 81501

Report Date:

March 1, 2022







Sanders Gravel Pit, Routt County, CO Traffic Impact Study

Contents

1.	Introduction	1
2.	Project Location and Description	1
3.	Trip Generation & Distribution	3
	3.1 Trip Generation	3
4.	Trip Distribution & Assignment	4
	4.1 Determination of Trip Distribution	4
	4.2 Assignment of Project Traffic	4
5.	Existing & Future Traffic Volumes	5
6.	Study Years Traffic Volumes	7
7.	Study Period Volumes	8
8.	Auxiliary Turn Lane Evaluation	12
9.	Intersection Sight Distance	12
10.	Summary and Recommendations	15

Appendix

- A. Gravel Pit & Mining Questionnaire
- B. Intersection Turning Movement Count Traffic Summaries
- C. Trip Generation



1. Introduction

APEX Consulting Engineers, LLC prepared this Traffic Impact Study (Study) for the proposed Sanders Gravel Pit (Project), located at 26650 Wheeler Lane, Routt County, CO, accessing County Road 129 from an existing access west of US Forest Service Trail 1180. The following sections describe the Project, traffic volumes, auxiliary turn lane assessments, access spacing, and sight distance evaluation for this intersection.

2. Project Location and Description

As shown in Figure 1, the proposed Project will be located north of Steamboat Springs, along Routt County Road 129. The Project will include a small gravel pit which will operate year-round with seasonal fluctuations to their production rate. The production rate is expected to be lowest from November to March. The site is expected to produce approximately 67,000 tons per year from 2022 to 2033.

The site is expected to go through two production phases before closure. The first phase is from 2022 through 2027 while the second phase is from 2028 to 2033. Although the production of the gravel pit will likely decrease during phase two, this report will assume the production stays constant for both phases. A detailed Gravel Pit & Mining Production Questionnaire, completed by the operator, is attached in Appendix A.







Sanders Gravel Pit, Routt County, CO Traffic Impact Study



The existing Project extents and site access location and adjacent private driveways are shown in Figure 2.



Figure 2 – Project Site Access Locations and Adjacent Access Points





3. Trip Generation & Distribution

3.1 Trip Generation

The ITE Trip Generation Manual does not include a land use code and trip data for gravel pit operations. Project trips were estimated from the Gravel Pit & Mining Production Questionnaire provided by the operator. The Project is expected to have two production periods throughout the year. Trip Generation is broken into low production and high production to accurately model the Project as trip distribution is expected to differ from high and low production.

Traffic engineering standards require conversion from trucks to passenger car equivalents (PCE). The following table shows the Project peak hour traffic volume calculation for the final Project phase.

Project Traffic Volume Calculations are summarized in Tables 1 and 2 as passenger car equivalent vehicles per hour (PCE-VPH). Complete calculations are provided in Appendix C. The traffic volumes in the table represent the estimated number of passenger car equivalents per hour of operation. Note that all staff will arrive within the same hour and not staggered throughout the day. Additionally, the number of trips per hour calculation, rounds up to the next integer to be conservative in the peak hour calculations. Additional trips to the site for maintenance, deliveries, fueling, etc. are assumed to occur outside of the peak hour and are not considered in the peak hour trip generation for the Project.

Traffic Type	Period	AM	PM	ADT
Staff	Entry	0	0	1
Stall	Exit	0	1	1
Small Trucks	Entry	1	1	4
Small Trucks	Exit	1	1	4
	Entry	0	0	0
Large Trucks	Exit	0	0	0
	TOTAL	2	3	10

Table 1 – Low Production Project Peak Hour Traffic Volumes (PCE-VPH)

Table 2 – High Production Pr	ject Peak Hour Traffic \	Volumes (PCE-VPH)
------------------------------	--------------------------	-------------------

Traffic Type	Period	AM	PM	ADT
Staff	Entry	0	0	4
Stall	Exit	0	4	4
	Entry	2	2	16
Small Trucks	Exit	2	2	16
	Entry	4	4	36
Large Trucks	Exit	4	4	36
	TOTAL	12	16	112





4. Trip Distribution & Assignment

4.1 Determination of Trip Distribution

The Project site had been operating as a gravel pit for a short period of time. Project trip distribution for the gravel pit is assigned to the Project accesses from the Gravel Pit & Mining Production Questionnaire provided by the owner. The detailed Project trip distribution is shown in Figure 3. Note that the L in each figure represents the low production conditions and the H represents high production conditions.





4.2 Assignment of Project Traffic

Project traffic determined from the trip generation calculation is assigned to the existing traffic network using the distributions from Figure 3. The resulting Project trip assignment is shown in Figure 4.







Figure 4 – Project Peak Hour Trip Assignment (PCE VPH)

5. Existing & Future Traffic Volumes

Peak hour intersection turning movement counts were conducted at Routt County Road 129 & Project Access on October 26, 2021.

Peak seasonal adjustment of 1.41 was used for existing through volumes for the high productivity period on Routt County Road 129 to account for the traffic counts being completed in October. The low productivity period will not use a seasonal adjustment factor.

Table 3 shows the monthly peak seasonal adjustments using a similar roadway with a CDOT continuous counting station.





Table 3 – Peak Season Adjustment Factors by Month

CDOT Count Station ID 15: SH 040A Traffic Data - South of Steamboat Springs													
STATION ID	CAL YR	JAN	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEP	OCT	NOV	DEC
209	2022	8680											
209	2021	8443	8597	9089	7860	9578	12318	14291	11914	11917	9499	8413	8135
209	2020	8857	8695	6700	4600	7169	10503	12590	13276	11639	9694	7485	7795
209	2019	8812	9299	8753	7009	8129	10730	12616	11968	11242	8719	7819	8459
209	2018	8575	9001	9015	7557	7850	9745	11587	11847	10351	8610	7822	8586
209	2017	8017	8765	8710	7364	8539	11665	13180	12078	11207	9264	7887	8392
209	2016	7869	9108	8460	6141	8311	11309	12262	10855	9629	7910	7798	7789
209	2015	7550	8014	8289	7097	7649					8561	6975	7153
209	2014	7111	7438	7711	6345	7642	10334	11791	10689	9498	7942	6573	7342
209	2013	6871	7516	7530	6086	7470	9974	11357	10760	9185	7615	6772	7186
209	2012	6781	6915	7374	6460	7610	9132	8425	9558	9117	7539	6714	6362
209	2011	6756	6827	7196	5848	6706	9242	10800	10456	9277	7561	6365	6987
209	2010	7113	7043	7803	6244	7075	9255	11036	10276	9043	7542	6390	6934
209	2009	7671	7760	7801	6806	7966	10070	11558	10723	9660	7792	6726	7022
209	2008	7817	7709	8114	7001	7978	10535	11974	11263	9994	9028	7397	7738
209	2007	7509	7507	7996	6906	8758	10925	12053	11647	10265	8945	7995	7605
209	2006	7188	7538	7705	6702	8058	10710	11964	10327	9533	8254	7314	7651
209	2005	7290	7482	7506	6373	7782	10187	11770	10804	9652	8066	7009	7217
209	2004	7041	7164	7586	6625	7684	10147	11600	10503	9654	8169	7267	7731
209	2003	7134	6870	7061	6473	7730	10283	11429	10774	9412	8649	6444	7254
Avera	ge	7,654	7,855	7,916	6,605	7,878	10,392	11,794	11,095	10,015	8,387	7,219	7,544
% of highes	t month	65%	67%	67%	56%	67%	88%	100%	94%	85%	71%	61%	64%
Peak Seaso	n Factor	1.54	1.50	1.49	1.79	1.50	1.13	1.00	1.06	1.18	1.41	1.63	1.56

Seasonal Adjustments

The existing peak hour traffic, adjusted for peak season, is represented in Figure 5. Count summaries are included in Appendix B.







Figure 5 – Existing Peak Hour Traffic adjusted for Peak Season (From counts 8/26/2021)

6. Study Years Traffic Volumes

Future background traffic is determined in this section.

The study years are 2022 and 2033. Routt County Road 129 is assumed to have a similar growth pattern as Highway 40 in Steamboat Springs. The Online Transportation Information System (OTIS) was used to find ADT values for 2019 counts & 2045 projected counts which are the basis for the following road segment growth factors:

		A	DT	Period	Avg.	1 - year	12 - year
Road	Segment	2020	2045	Growth Factor	Annual Growth Rate	growth factor (2021-2022)	growth factor (2021-2033)
SH 40	Both Sides	9,200	11,155	1.213	0.78	1.008	1.098

Table 4 – Road Segment Growth





These growth factors were used to determine future peak hour background traffic volumes on Routt County Road 129.

7. Study Period Volumes

Figures 6 and 8 demonstrate the future background traffic volumes by adjusting the traffic in Figure 5 with the growth factors from Table 3. Figures 7 and 9 show total peak hour traffic which consist of future background traffic with Project traffic.



Figure 6 – Background Peak Hour Future Traffic (Year 2022)







Figure 7 – Total Peak Hour Future Traffic (Year 2022 PCE VPH)





Figures 8 and 9 show the predicted traffic volumes for year 2033.



Figure 8 – Background Peak Hour Future Traffic (Year 2033)













8. Auxiliary Turn Lane Evaluation

Routt County Road 129 is a north south road with milepost markings increasing from south to north and matches the CDOT classification of R-B (Rural Highway).

The need for auxiliary lanes was based on the turn lane warrants listed in the SHAC. The following table shows the data and criteria necessary to identify the need for exclusive right-turn and left-turn deceleration lanes at the intersections in the Study area.

Note that all turning volumes are in terms of Passenger Car Equivalents (PCE).

Routt County Road 129 & Project Access Year 2033 Condition Speed Limit = 45 mph									
Auxiliary Lane	Turning Volume (VPH)	CDOT Auxiliary Lane Requirements	Lane Required?						
SB Left Turn Deceleration Lane (inbound)	4 (PM)	Greater than 10 vph	NO						
NB Right Turn Deceleration Lane (inbound)	9 (AM)	Greater than 25 vph	NO						
WB Left Turn Acceleration Lane (outbound)	14 (PM)	May be req'd if benefit to safety and operations. Generally not required if speed < 45 mph	NO						
WB Right Turn Acceleration Lane (outbound)	4 (AM)	More than 50 vph, with speed limit over 40 mph	NO						

Table 5 – Comparison of Turning Volumes toTurn Lane Requirements

Auxiliary turn lanes are not required for this Project.

9. Intersection Sight Distance

Routt County Road 129 is a 2-lane roadway with a posted speed limit of 45 mph with a varying grade from 0% up to 7%. Although most of the roadway has a grade less than 3%, a reduction in sight distance will be used for the section of road south of the access since it is the only section with grades greater than 3%. The study will not use increases in sight distance that are allowed for grades greater than 3%. The sight distance analysis is based on a single unit truck.

The required sight distance for a vehicle traveling on the highway toward the access is 400 feet for a 45 mph speed limit (from Table 4-1 SHAC). The required sight distance with the adjustment factor is 320 feet. The observed sight distance is greater than 400 feet while travelling north and south to the access. Refer to Images 1 through 4.





Note that the sight distance along the south side of the access is not maintained for the entirety of the roadway. Recommendations on how to improve the existing access are in the next section of this report.



Image 1 – Looking North Along Routt County Road 129

Image 2 – Looking South Along Routt County Road 129





Sanders Gravel Pit, Routt County, CO Traffic Impact Study



The required sight distance for single unit trucks entering the roadway with a posted speed limit of 45 mph is 585 feet per SHAC, Table 4-2. The required sight distance with the adjustment factor is 468 feet. The observed sight distance is greater than 585 feet in both directions, shown in Images 3 and 4.



Image 3 – Looking North from Project Access

Image 4 – Looking South from Project Access





Sanders Gravel Pit, Routt County, CO Traffic Impact Study



10. Summary and Recommendations

- The proposed Project will increase the traffic volumes during peak hours by 11 AM trips and 15 PM trips. Note that these volumes are in Passenger Car Equivalents (PCE).
- Auxiliary turn lanes are not required at the Project Access.
- The tall brush/vegetation circled in Image 1, on the east side of the road and within the right of way, for a distance 400' south of the access, should be cleared to provide a wider view of the access road for northbound traffic.
- Installation of MUTCD sign W8-6 or W11-10 south of the Project Access is recommended to improve the safety of the intersection by providing northbound traffic notice of the upcoming intersection. The location of the sign should be along the section of roadway where sight distance is not maintained, which is roughly 500 feet from the access.



Appendix A - Gravel Pit & Mining Questionnaire



Gravel Pit & Mining Production Questionnaire

Please provide as much information as possible and attach appropriate documents.

Project Name: Sanders Gravel Pit
Project Location/Address: Steamboat Springs, CO 80477
Company Name: Tara Sanders
Person Completing this Form: Name: Tony Waldron
8N R85W SB in Routt County Title: Project Consultant
rce 1 # 924331003 Phone Number: 303-263-6902
Date: 9/29/21

Overall Production Schedule

- 1. How many different production phases will occur before pit closes?
- 2. What are the years and production amounts?

 Phase
 Range of Years
 Production Amount (Tons per Year)

 1
 J0J2 thru J0J7
 67,000

 2
 J0J8 thru J0J3
 67,000

 3

Please complete one of the following pages of detailed information for each Phase

Information from Similar Sites

Please provide any information or data from similar sites that could be used to support the information on these data sheets.

Due to site location, weather will likely be a limiting factor for production from November thru MARCH/April. Therefore, most production will occur from April thru October.



Detailed Information – Phase 1

Production Years: 2022 thru 2027

Limiting Factor for annual production (permit, etc): (please attach appropriate document if available)

Does the Production Rate vary over the course of the year:

If so, provide the following information for three possible production periods

Market Conditions / Demand

April thru for October Production will like ! NCREGGE

If not, put your answers in the average column

	Production Periods									
	Low	Average	High							
	NOV. thru March	thru	April thrubet.							
ay: :	1 8:00 am 4:00 pm		17:00 am 5:00 pm							
Ý	1/week		/							
day			12							
per										
ess	0-4		/6							
	4		5							
			10							
	50°/0 50°/0		20 °/0 20 %							
	=100%	=100%	=100%							

discussion with Sanders Pit team

Months of the year for each period:

Daily Trip Generation

Number of on-site workers per day: On-site worker arrival time (s): On-site worker departure time (s):

Number of other site visits per day (Maintenance, deliveries, fueling, customers, supervisors, etc)

Number of large dump trucks per day (greater than 40-ft long)

Number of medium dump trucks per day (between 20-ft & 40-ft long)

Number of small trucks per day (less than 20-ft long)

Number of Work days per week

Number of Work hours per day

<u>Trip Distribution</u> % of trips to/from North % of trips to/from South % of trips to/from East % of trips to/from West



discussion with Sanders Pit team

Detailed Information – Phase 2

Production Years: 28 thru 33

Limiting Factor for annual production (permit, etc): (please attach appropriate document if available)

Does the Production Rate vary over the course of the year:

If so, provide the following information for three possible production periods

May not occur due to lack of reserves

Production will likely increase from April thru October

If not, put your answers in the average column

	Production Periods							
	Low	Average	High					
Months of the year for each								
period:	NOV. thru <u>March</u>	thru	Heril thru Oct.					
Daily Trip Generation	1		U					
Number of on-site workers per day:			7					
On-site worker arrival time (s):	1.00 am							
On-site worker departure time (s):	<u>4:00 pm</u>		<u>2:00 pm</u>					
Number of other site visits per day (Maintenance, deliveries, fueling, customers, supervisors ,etc)	1/week		/					
Number of large dump trucks per day (greater than 40-ft long)		an a						
Number of medium dump trucks per day (between 20-ft & 40-ft long)								
Number of small trucks per day (less than 20-ft long)	<u> </u>		1C					
Number of Work days per week	4	Constant of the second s						
Number of Work hours per day	8		10					
Trip Distribution	- 01		0.01					
% of trips to/from North	5070		2010					
% of trips to/from South	50%0	an and the second s	20%					
% of trips to/from East	······································							
% of trips to/from West								
	=100%	=100%	=100%					
			80% to/from south per					



Appendix B – Count Summaries Intersection Turning Movement Count Summary

Sanders Gravel Pit					
Routt County					
Project Access					
Routt County Rd 129					



Count Date: 10/27/2021

Intersection 1 - Project Access & Routt County Rd 129

		Project Access - (EB)		Project Access - (WB)		Routt County Rd 129 - (NB)			Routt County Rd 129 - (SB)					
		Left	Through	Right	Left	Through	Right	Left	Through	Right	Left	Through	Right	Sums
	7:00	-	-	-	0	-	0	-	18	0	0	20	-	38
	7:15	-	-	-	0	-	0	-	10	0	0	22	-	32
	7:30	-	-	-	0	-	0	-	19	0	0	49	-	68
	7:45	-	-	-	0	-	0	-	22	3	1	26	-	52
Σ	8:00	-	-	-	0	-	0	-	16	0	1	31	-	48
A	8:15	-	-	-	0	-	2	-	16	0	0	23	-	41
	8:30	-	-	-	1	-	1	-	25	0	0	22	-	49
	8:45	-	-	-	0	-	0	-	12	0	0	17	-	29
	Peak	-	-	-	0	-	2	-	73	3	2	129	-	200
	Sums	-			2		76			131			209	
	16:00	-	-	-	0	-	0	-	28	0	0	17	-	45
	16:15	-	-	-	0	-	0	-	24	0	0	22	-	46
	16:30	-	-	-	0	-	0	-	19	0	0	19	-	38
	16:45	-	-	-	2	-	0	-	26	1	2	14	-	45
Σ	17:00	-	-	-	2	-	0	-	33	0	0	16	-	51
E	17:15	-	-	-	0	-	0	-	28	1	0	11	-	40
	17:30	-	-	-	0	-	0	-	29	0	0	12	-	41
	17:45	-	-	-	0	-	0	-	25	0	0	6	-	31
	Peak	-	-	-	4	-	0	-	102	1	2	71	-	100
	Sums		-			4			103			73		180



Low Production Project Average Daily Traffic (ADT) Calculations Hrs of Operation 7:00 am -5:00 pm

Trip Information	Purpose		Workers	Other Visits	Material Handling		
	Vehicle Type		Passenger Vehicle	Small Trucks <20 ft long	Small Trucks <20 ft long	Large Trucks >40 ft long	Total Peak Hour Trips
	Passenger Car Equivalent Factor		1	1	1	3	
Low Production	Number of Vehicles / Day		1	0	4	0	
	PCE Number of Vehicles / Day		1	-	4	-	
	Trucking Hours / Day		N/A	10	10	10	
	PCE Number of Vehicles / Hour		1	-	1	-	
	PCE Number of Trips / Hour		1	-	2	-	
	AM Peak Period Trip	PCE in	0	-	1	-	1
	(2 trips/veh)	PCE out	0	-	1	-	1
	PM Peak Period Trips	PCE in	0	-	1	-	1
	(2 trips/veh)	PCE out	1	-	1	-	2

High Production Project Traffic Volume Calculations

Trip Information	Purpose		Workers	Other Visits	Material Handling		
	Vehicle Type		Passenger Vehicle	Small Trucks	Small Trucks	Large Trucks	Total Peak Hour Trips
	Passenger Car Equivalent Factor		1	1	1	3	
Low Production	Number of Vehicles / Day		4	1	16	12	
	PCE Number of Vehicles / Day		4	1	16	36	
	Trucking Hours / Day		N/A	10	10	10	
	PCE Number of Vehicles / Hour		4	N/A	2	4	
	PCE Number of Trips / Hour		4	-	4	8	
	AM Peak Period Trip	PCE in	0	-	2	4	6
	(2 trips/veh)	PCE out	0	-	2	4	6
	PM Peak Period Trips	PCE in	0	-	2	4	6
	(2 trips/veh)	PCE out	4	-	2	4	10